<u>Tinted Disco</u> (Includes Pastel, Neon and KT Series)







APPLICATIONS LIST FOR TINTED DISCO

- 1. Fabric Printing
- 2. Toys
- 3. Cosmetic Gels
- 4. Floral Designs
- 5. Ceramic Decoration (after firing)
- 6. Paints (water based systems)
- 7. Christmas Ornaments and Decorations
- 8. Greeting Cards (water based systems)
- 9. General Crafts
- 10. Screen Printing (water based systems)

TECHNICAL DATA - TINTED DISCO

Available Colors	Nominal Dominant Wavelength (nm)	Nominal Thickness (mils/µm)	Nominal Yield (sq. in./lb)
VKT	465	1.1/28	22,000
BKT	485	1.2/30	20,000
GKT	555	1.3/33	18,000
ZKT	590	1.4/36	16,000
Pastels/Neon	555/485	1.3/33	18,000

Fade	Color change at 232 hrs in a UVA-340
Resistance	florescent chamber.

Property	Nominal Value		
1. Specific Gravity	1.2		
2. Color Shift Temperature	225°F/107°C		
3. Color Loss Temperature	420°F/215°C		

Tint Stability (Bleed)							
Challenge Solvent	Black	Blue	Green	Red	Yellow		
Ethyl Acetate	Fail	Fail	Fail	Fail	Fail		
Hexane	Pass	Pass	Pass	Pass	Pass		
Isopropyl Alcohol	Pass	Pass	Pass	Pass	Pass		
MEK	Fail	Fail	Fail	Fail	Fail		
Perchloroethylene	Pass	Fail	Fail	Fail	Fail		
Toluene	Fail	Fail	Fail	Fail	Fail		
Trichloroethylene	Fail	Fail	Fail	Fail	Fail		
Water	Pass	Pass	Pass	Pass	Pass		

The above information is given for guidance only. While it is based on scientific evaluation, and is believed to be reliable, Glitterex Corporation makes no warranties, whether expressed or implied, including warranties of merchantability and of fitness for a particular purpose for these products, since among other reasons the conditions of storage and use are beyond our control. No statements or recommendations contained herein are to be construed as inducements to infringe any patent.

Glitterex Corporation
7 Commerce Drive
Cranford, NJ 07016 U.S.A.
Tel: (908) 272-9121 Fax: (908) 272-9191